



GILL

WINDSONIC 75

High quality, general purpose, ultrasonic anemometers.

PRODUCT OVERVIEW

Gill WindSonic 75 is a low-cost, high speed anemometer, which utilises Gill's proven ultrasonic technology to provide wind speed and direction data via one serial or two analogue outputs.

WindSonic is WMO-compliant for gust measurement. With a robust, corrosion-free polycarbonate housing, this small, lightweight wind sensor is recommended for use in harsh environmental conditions and is particularly suited to marine & offshore (ships, data buoys) and land based installations.

KEY FEATURES & BENEFITS

- 01** Accurate wind speed and direction measurement from a single solid-state sensor.
- 02** 0–75 m/s (146 knots) wind speed range with full 0–360° direction coverage.
- 03** WMO-compliant gust measurement using rolling averages.
- 04** No moving parts, minimising maintenance and reducing lifetime costs.
- 05** Corrosion-free design with proven reliability
- 06** Low power consumption with fast start-up.

TYPICAL APPLICATIONS

- Remote weather monitoring stations
- Building controls
- Data buoys
- Marine vessels
- Small airports & helipads
- Road & rail tunnels
- Environmental field sites
- Ports & harbours
- Mobile weather monitoring vehicles
- Coastal weather monitoring stations



WindSonic ultrasonic anemometers offer high accuracy, low cost wind measurement.

WINDSONIC 75

High quality, general purpose, ultrasonic anemometer.

TECHNICAL SPECIFICATION

Wind Speed	
Range	0 - 75 m/s (146 knots)
Accuracy	<2% RMSE or 0.2m/s RMSE, whichever is greater (0-20m/s) <3% RMSE (20-60m/s) <5% RMSE (60-75m/s)
Resolution	0.01 m/s (0.02 knots)
Response time	0.25 seconds
Starting threshold	0.01 m/s
Wind Direction	
Range	0 - 360° (no dead band)
Accuracy	<2° RMSE (0-75m/s)
Resolution	0.1° Option 1, 2 & 3 (output at 0, 1 or 2 decimal places) 0.1° Option 5
Response time	0.25 seconds
Measurement	
Ultrasonic output	0.25, 0.5, 1, 2 or 4 Hz
Parameters	Wind speed & direction or U and V (vectors)
Units of measurement	m/s, knots, mph, kph, ft/min
Anemometer status	For unit diagnostics
Outputs	
Option 1 interface	RS232
Option 2 interfaces	RS232, RS422, RS485**
Option 3 interfaces	RS232, RS422, RS485** Analogue 0-5 V or 0-20 mA 4-20
Option 1, 2 & 3 protocols	ASCII, NMEA 0183
Option 5	Modbus RTU, 2-wire RS-485
Baud Rate	2400 to 38400
Mechanical	
External	LURAN S KR 2861/1C ASA/PC
Size	142 mm x 163 mm
Weight	0.5kg




Power Requirement	
Anemometer	12-30 VDC Option 1 & 2 9-30 VDC Option 5
Current drain	Dependent on option selected e.g. up to 44 mA @ 12V (4-20 mA) Refer to manual for further advice Start up time < 5 seconds
Environmental	
Protection class	IP66
Operating	-35°C to +70°C
Storage temperature	-40°C to +80°C
Operating humidity	< 5% to 100% RH
Precipitation	300 mm/hr
Operational	
Warranty	24 months
Factory calibration	Traceable to National Standards
Accessories	
Pipe mounting (optional)	44.45 mm (1.75 in) diameter
Wind software	Display / logging*
Cables (optional)	Available to match output option
Display (optional)	See Gill Display datasheet

* Download software free from gillinstruments.com

** 2-wire is point-to-point only

WINDSONIC 75

High quality, general purpose, ultrasonic anemometer.



**Designed and manufactured in the UK by
Gill Instruments Limited.**

**Specifications may be subject to
change without prior notice**

GILL

1405-0035 Issue 10
© 2026 Gill Instruments
gillinstruments.com

MORE INFO

For more information about Gill's WindSonic range,
please email contact.gi@gill.group